

CE IP 20

1500

Surface down light

TECHNICAL DATA

Mounting: Surface
Body: Diecast Aluminium
Colour: White, Black
Protection: IP20
Operation temperature: 0-35

ELECTRICAL DATA

Power: 9 / 15 / 20 / 35 / 40W
Type of Equipment: ED, Dimmable on request
Power factor: 0.9<

OPTICAL DATA

Beam Angle: 60
Way of lighting: Direct
Diffuser: Acrylic
CCT: 3000K, 4000K, 5000K
CRI: 80<

GENERAL DATA

Warranty: 5 Years
Application : Office, Residential, Hospitals



Code	Type of Equipment	Power	CRI / Ra	Luminous Efficacy	Lumens	Operating Temperature range
1500.XX09.XXXX	ED/DIM	9	80/90	100	900	0 - 35
1500.XX15.XXXX	ED/DIM	15	80/90	100	1500	0 - 35
1500.XX20.XXXX	ED/DIM	20	80/90	100	2000	0 - 35
1500.XX35.XXXX	ED/DIM	35	80/90	100	3500	0 - 35
1500.XX40.XXXX	ED/DIM	40	80/90	100	4000	0 - 35

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.

The operating temperature ranges apply only to luminaires used in the outdoor environment.

Power tolerance +/- 5%.

Colour temperature tolerance +/- 5%.

Led Waves Lighting reserves right to introduce any construction changes and improvements into the lighting.

ORDER DETAILS

1 5 0 0 . X X 0 9 . X X X X

Family

CCT /CRI

0	827
1	830
2	840
3	850
4	860
5	927
6	930
7	940
8	950
9	960

DIM

0	ED
1	1-10/0-10
2	Phase cut
3	Dali
4	Other

POWER

Body & Reflector Finish

00	White Polished
01	White Black
02	White Gold
03	White Silver
10	Black Polished
11	Black Black
12	Black Gold
13	Black Silver

Ingress Protection

Beam Angle

1 IP20

3 Flood

Code

Dimension (mm)

1500.XX09.XXXX	D 90 X H 90
1500.XX15.XXXX	D 110 X H 120
1500.XX20.XXXX	D 130 X H 152
1500.XX30.XXXX	D 170 X H 185
1500.XX40.XXXX	D 193 X H 193



Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.

The operating temperature ranges apply only to luminaires used in the outdoor environment.

Power tolerance +/- 5%.

Colour temperature tolerance +/- 5%.

Led Waves Lighting reserves right to introduce any construction changes and improvements into the lighting.