

CE IP 20

7250

## Spike light

### TECHNICAL DATA

**Mounting:** Surface  
**Body:** Diecast Aluminium  
**Colour:** White, Black, Dark Grey  
**Protection:** IP65  
**Operation temperature:** 0-50

### ELECTRICAL DATA

**Power:**  
**Type of Equipment:** ED, Dimmable on request  
**Power factor:** 0.5<

### OPTICAL DATA

**Beam Angle:**  
**Way of lighting:** Direct  
**Diffuser:** PC  
**CCT:** 3000K, 4000K, 5000K  
**CRI:** 70/80<

### GENERAL DATA

**Warranty:**  
**Application :** Parking, Parks, Gardens



Code	Type of Equipment	Power	CRI / Ra	Luminous Efficacy	Lumens	Operating Temperature Range
7250.5205.0114	ED/DIM	5W	70/80	80	2400	0 - 50

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.


The operating temperature ranges apply only to luminaires used in the outdoor environment.

Power tolerance +/- 5%.

Colour temperature tolerance +/- 5%.

Led Waves Lighting reserves right to introduce any construction changes and improvements into the lighting.

## ORDER DETAILS




### Code

7250.5205.0114

### Dimension (mm)

D 50 X H 120



## PHOTOMETRIC DISTRIBUTIONS

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.

The operating temperature ranges apply only to luminaires used in the outdoor environment.

Power tolerance +/- 5%.

Colour temperature tolerance +/- 5%.

Led Waves Lighting reserves right to introduce any construction changes and improvements into the lighting.