

CE IP 20

1044

Recessed down light

TECHNICAL DATA	Mounting: Recessed Body: Diecast Aluminium Colour: White, Black Protection: IP20 Operation temperature: 0-35
ELECTRICAL DATA	Power: 3W Type of Equipment: ED, Dimmable on request Power factor: 0.5<
OPTICAL DATA	Beam Angle: 30 Way of lighting: Direct Diffuser: Acrylic CCT: 3000K, 4000K, 5000K CRI: 80<
GENERAL DATA	Warranty: 3 Years Application : Office, Residential, Hospitals



Code	Type of Equipment	Power	CRI / Ra	Luminous Efficacy	Lumens	Operating Temperature range
1044.XX03.XXXX	ED/DIM	3	80/90	90	270	0 - 35

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.
The operating temperature ranges apply only to luminaires used in the outdoor environment.
Power tolerance +/- 5%.
Colour temperature tolerance +/- 5%.

Led Waves Lighting reserves right to introduce any construction changes and improvements into the lighting.

ORDER DETAILS

1 0 4 4 . X X 0 3 . X X X X

Family

CCT /CRI

0	827
1	830
2	840
3	850
4	860
5	927
6	930
7	940
8	950
9	960

DIM

0	ED
1	1-10/0-10
2	Phase cut
3	Dali
4	Other

POWER

Body & Reflector Finish

00	White Polished
01	White Black
02	White Gold
03	White Silver
10	Black Polished
11	Black Black
12	Black Gold
13	Black Silver

Ingress Protection



Beam Angle

0	IP00
1	IP20
2	IP44
3	IP54
4	IP65
5	IP67
6	IP68

0	Very Narrow
1	Narrow
2	Medium
3	Flood
4	Wide flood

1044.XX03.XXXX

D 45 X H 50 38



PHOTOMETRIC DISTRIBUTIONS

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.

The operating temperature ranges apply only to luminaires used in the outdoor environment.

Power tolerance +/- 5%.

Colour temperature tolerance +/- 5%.

Led Waves Lighting reserves right to introduce any construction changes and improvements into the lighting.